

precote 200

resilient under-head sealant

Description

precote 200 is a high resilient under-head sealant with good adhesion to seal the mating surfaces of screws, plugs and rivets. The coating is completely dry and non tacky. The sealing performance is obtained immediately after assembly.

Application

precote 200 is designed as an under-head sealant for flange head and collar screws. precote 200 can also be used for sealing and isolation requirements with rivets. Depending on the design of the flange / collar reusability at room temperature is given. precote 200 is designed to replace O-rings and gasket seals.

Properties

- Dry and tack-free coating
- Captive sealing part
- Simple handling
- Good resistance against water based fluids
- Reusable at room temperature
- Physiologically harmless
- Applicable from -40°C to +100°C (-40°F to 212°F)

Technical data

- Colour blue
- Hardness (Shore A) 50-65
- On part shelf life min 4 years
at max.30°C and
max. 65% relative humidity

Storage- and transport conditions can be taken from the oT-packaging indication.

01/12

Guarantee: As we do not know the specimen, dimensions, materials, combinations, surface conditions etc. of the threads in question, it is absolutely essential to run quality tests prior to general use to make sure about the required performance under field conditions. Our guarantee is confined to supplying precote in proper quality. In view of the fact that processing of precote by the coating partner and the application of precote coated parts are beyond our knowledge and influence we cannot guarantee for the quality of parts coated with precote and assemblies made thereof. We accept liability for the fitness of our products for particular purposes and liability for particular qualities of our products only in the event that we have accepted such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequential damage, shall be excluded.

Voraussetzungen für Unterkopfdichtung mit precote 200 bei Schraubenköpfen

condition for under head sealing with precote 200 at screw heads.

